

## 5130



**Tally**  
**DASCOM**

Tally Dascom's 5130 flat bed printer is designed to handle the most difficult cut sheet forms easily and reliably. For those applications where there is a requirement for a mixture of cut sheet and continuous paper there is a version with tractors. The printer is ideal for front office applications in banks, retail outlets, doctor's surgeries, where a wide range of media is used.

The printer's flat bed design provides reliable paper handling. With advance features such as "place anywhere" Automatic Paper Alignment, Auto Gap Adjustment and Automatic paper position sensing 5130 offer unsurpassed ease of use. Media placed "anywhere" on the input shoot is automatically aligned to the print position and without

### Highlights at a glance:

- Prints on thick documents (up to 6 mm)
- "Place Anywhere" automatic alignment of forms and passbooks
- Automatic gap adjustment of print head
- Supports a wide variety of media
- Tractor model
- USB, Parallel and Serial Interface standard with auto select function

further need for paper thickness or print position adjustment the document is presented for printing.

With up to 400 characters per second print speed the 5130 rapidly processes media of diverse types ranging from passbooks and cheques to receipts and information sheets up to 9.4 inches (245 mm) wide. The 24 pin print head ensures that every document is produced in high quality with crisp text.

The 5130 is robust, durable, and easy to use supporting a wide range of on demand printing applications at the front office.

### Configurations:

- **5130**      **Standard model**
- **5130 P**    **Passbook model**
- **5130 P**    **Passbook model with tractor**

## 5130

<b>Print Speed</b>	400 cps (Fastest Draft); 300 cps (Draft), 100 cps (LQ) at 10 cpi
<b>Resolution</b>	Up to 360 x 360 dpi
<b>Character Density</b>	10, 12, 15, 16.6, 17.1, 20, 24 cpi
<b>Line Density</b>	5, 6, 8 lpi
<b>Printhead Life</b>	400 million strokes
<b>Memory</b>	64 kB
<b>Standard Connectivity</b>	Parallel (Bi-directional), Serial RS 232 und USB 2.0
<b>Standard Emulation</b>	IBM ProPrinter XL24, Epson (ESC P/2), Olivetti PR2/PR40/PR50/PR2845
<b>Fonts</b>	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Elite, OCR-A/B
<b>Consumables</b>	Ribbon: 4 million characters
<b>Standard Paper Handling</b>	Cut sheet from the front with automatic alignment Additional rear push tractor (option on 5130 P model; standard on 5130 T model)
<b>Number of Copies</b>	1 original + 4 copies
<b>Paper Type</b>	Cut sheets, multi-part forms, passbooks with a thickness up to 2,8 mm (standard model) and up to 6 mm (5130 P) fanfold paper (option on 5130P ans standard on 5130 P tractor model)
<b>Paper Weight</b>	52 - 157 g/m <sup>2</sup> (Cut sheet) 64 - 100 g/m <sup>2</sup> (Fanfold)
<b>Paper Size</b>	Width: 60 to 245 mm (Cut sheet) Width: 101,6 to 241,3 mm (Fanfold)
<b>Physical Weight</b>	9 kg
<b>Physical Size</b>	384 x 313 x 203 mm (W x D x H)
<b>Acoustic (ISO 7779)</b>	< 55 dB(A)
<b>Power Voltage</b>	230 V - 50/60 Hz
<b>Power Consumption</b>	3,9 Watt Stand-By
<b>Temperature</b>	+5° to +40° C; 10% to 90% humidity
<b>Workload</b>	5.000 transactions per month
<b>MTBF</b>	10.000 hours
<b>Drivers</b>	Windows 2000/XP/Vista/7 and Server 2003/2008

### DASCOM GB Limited

Hart House, Priestley Road

Basingstoke, Hampshire RG24 9PU

Tel: +44 1256 481481 – Fax: +44 1256 481400

info.gb@dascom.com – www.dascom.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 