

T2150

Fast, reliable class leading printers



Tally

The T2150 and T2250 are highly featured, reliable and stylish machines. Performance and workload, ergonomics, maintainability, excellent price – everything has been incorporated to ensure they are the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors. If 'tear at top of form' is inadequate for your application, the T2150S features a cutting device which separates forms automatically.

- **Print speeds up to 750 cps**
- **26,000 pages per month workload**
- **80 columns**
- **24 pin print head produces excellent print quality**
- **Automatic gap adjustment and quick tear**
- **Straight through paper path for easy forms loading**
- **Parallel and Serial interfaces standard**
- **LAN, IBM AS400/iSeries, Mainframe optional**

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 52dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

Available Configuration:

T2150 Standard Product

T2150S with Automatic Cutter

LA550N DEC Compatible Version

SERIAL MATRIX
PRINTERS

MOBILE
PRINTERS

THERMAL
PRINTERS

LINE MATRIX
PRINTERS

LASER
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

T2150





Print Speed	Draft: 500cps; NLQ: 180cps; LQ: 90cps
Resolution	Up to 360 x 360dpi
Printhead Life	400 million characters
Memory	128Kb
Standard Connectivity	Parallel (bi-directional) and serial RS232
Optional Connectivity	Serial current loop (20mA), Ethernet 10/100 Base T, USB Parallel Adapter, HostCom pocket coax matrix for IBM mainframe HostCom pocket twinax for AS400, iSeries, System 3X
Standard Emulation	IBM proprinter XL24, Epson LA2550, Tally MTPL + barcode + LCP
Optional Emulation	DEC LA75; MT50 (Diskette and manual program packs)
Fonts	HS draft (sans serif), draft (sans serif), Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B*, 19 barcodes and large character printing. Range of Arabic fonts (Arabic model)
Consumables	Ribbon: 3.6 million characters
STD Paper Handling	Push tractors with paper parking and automatic gap adjustment (AGA). Cut sheet front insertion with AGA
Opt'l Paper Handling	Additional push tractor, front. Additional push tractor, rear. Front single bin automatic sheet feeder. Paper cutting device (2150S only)
Paper Type	Continuous forms, Cut sheet
Paper Weight	Continuous forms 60-120gsm; Cut sheet 80-120gsm
Paper Size	420mm max
Physical Weight	9Kg
Physical Size	(HxWxD): 300x460x295mm
Power Voltage	230V
Power Consumption	40W printing
Workload	26,000 pages per month
Number of Copies	Up to 6 part forms
Temperature	+10° to +35°C
Humidity	20% to 80%
Acoustic	53dB(A)
Warranty	2 years, on-site

DASCOM GB Limited
ViewPoint, Basing View,
Basingstoke, Hampshire RG21 4RG
Tel: +44 (0) 1256 481481
Fax: +44 (0) 1256 481400

www.dascom.com

All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2009 DASCOM Europe GmbH
Ver. 1.0
Printed Date: 01.04.10

SERIAL MATRIX PRINTERS 
MOBILE PRINTERS 
THERMAL PRINTERS 
LINE MATRIX PRINTERS 
LASER PRINTERS 