

## T2280+

**High speed, rugged design for heavy duty operation**



*Tally*

The T2265+ and T2280+ are undoubtedly at the pinnacle of serial impact printing, representing the peak of performance in their respective speed segments. They are not just sprinters; reliable, heavy workload output is guaranteed for the many years following their purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Fully automatic operation instills operator confidence and virtually eliminates errors caused by poor user intervention. Front feed provides all the benefits of easy forms installation, coupled with reliable paper transport.

- **Print speeds up to 1000 cps**
- **Full range of automatic features minimising operator intervention**
- **Ideal for ,On-Demand' and ,Batch' applications with zero tear for no wasted forms**
- **Straight through paper path for easy forms loading**
- **Parallel and Ethernet (10/100BaseT) standard.**
- **Optional Serial RS232, IBM AS400/iSeries Mainframe Ethernet IPDS**
- **Straight through paper path for easy forms loading**
- **Compatible with a wide range of operating systems including Windows, UNIX, DOS, SAP R3 and legacy systems**

The products are well matched to Microsoft Windows applications, and entirely suited to other host operating environments, including legacy systems. The T2265+ and T2280+ printers are the first high speed matrix printers to incorporate Ethernet on-board.

Available Configuration:

T2280+  
T2280+ 2T with two additional tractors  
LA800+ DEC compatible version

SERIAL MATRIX  
PRINTERS

MOBILE  
PRINTERS

THERMAL  
PRINTERS

LINE MATRIX  
PRINTERS

LASER  
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

## T2280+

<b>Print Speed</b>	Draft: 800cps; NLQ: 222cps; LQ: 111cps
<b>Printhead Life</b>	500 million characters
<b>Throughput</b>	(ECMA 132 @ 10dpi) Letter Performance:626 pages per hour; Spreadsheet:389 pages per hour
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Memory</b>	128Kb
<b>Standard Connectivity</b>	Bi-directional parallel plus Ethernet 10/100BaseT with 128Kb buffer
<b>Optional Connectivity</b>	Serial RS232, adapters, Ethernet IPDS: USB parallel adapter IBM proprinter
<b>Standard Emulation</b>	MTPL + barcode/LCP, Epson LQ (Esc P/2), IBM ProPrinter XL24e
<b>Optional Emulation</b>	MT50, MT460, Digital/Compaq model (LA800) contextual Arabic
<b>Fonts</b>	Draft, Copy Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B*, 19 Barcodes and scaleable LCP Font. Range of Arabic fonts (Arabic mode)
<b>Consumables</b>	Ribbon: 20 million characters
<b>STD Paper Handling</b>	Push tractors with paper parking and AGA; 2nd rear push tractor - 2280-2T only, 1+1 copies; Cut sheet front insertion with AGA
<b>Optional Paper Handling</b>	2nd front tractor (user installable); Dual bin automatic sheet feeder*, 190 sheets per bin; Face down output bin*; Paper cutting device, paper pedestal; Front feed sheet feeder, 190 sheets capacity
<b>Paper Type</b>	Continuous forms, cut sheets
<b>Paper Weight</b>	Continuous forms: 60-120gsm; Cut sheet: 60-90gsm
<b>Paper Size</b>	Cut sheet: 100 to 420mm wide
<b>Physical Weight</b>	Approximately 19Kg
<b>Physical Size</b>	(HxWxD): 277x623x430mm
<b>Power Voltage</b>	230V
<b>Power Consumption</b>	75W printing
<b>Workload</b>	50,000 pages per month
<b>Number of Copies</b>	Up to 6 part forms. (1+1 for rear tractors of 2280-2T)
<b>Drivers</b>	Windows 9x/ME, 2000, 2003 Server, XP, Vista and SAP
<b>Temperature</b>	+10° to +35°C
<b>Humidity</b>	20% to 80%
<b>Acoustic</b>	57dB(A)
<b>Warranty</b>	2 years, on-site





**Note \***The dual bin sheet feeder and face down output bin are unsuitable for use with the 2280-2T. Exceeding the monthly duty cycle will not void the warranty if DASCOM consumables and maintenance kits are used.

**DASCOM GB Limited**  
ViewPoint, Basing View,  
Basingstoke, Hampshire RG21 4RG  
Tel: +44 (0) 1256 481481  
Fax: +44 (0) 1256 481400

[www.dascom.com](http://www.dascom.com)

All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2009 DASCOM Europe GmbH  
Ver. 1.0  
Printed Date: 01.04.10

SERIAL MATRIX PRINTERS   
MOBILE PRINTERS   
THERMAL PRINTERS   
LINE MATRIX PRINTERS   
LASER PRINTERS 