

# T2348

**Nimble, quiet workhorse**



*Tally*

**High-speed printing** - At 10 cpi, print speed ranges from 113 cps for letter quality to 432 cps for high speed draft quality. A 24 pin print head offers high speed with excellent quality.

**Software compatibility** - Compatible with the IBM Proprinter XL24E and Epson ESC/P2 command sets.

**Multiple fonts** - The printer has nineteen resident fonts: Ten bitmap fonts - Courier 10, Pica 10, Prestige Elite 12, Boldface PS, OCR-B, OCR-A, Correspondence, Compressed, Draft and High-speed Draft, and nine outline fonts - Timeless, Nimbus Sans and Courier, each in upright, italic and bold.

- 136 column
- Auto tear off
- Auto load
- Printhead protection
- USB interface (model option)
- Lan interface (model option)
- Auto interface switching on multiple I/F versions

**Large print buffer** - 128k bytes are available in total for strong input data and downloading fonts. A large input data buffer allows you to send files to the printer and return quickly to your application.

**Simple switching of paper types & Auto tear-off** - Parking continuous forms makes it easy to switch between continuous forms and single sheets. Continuous forms are automatically fed up to the tear-off position at the end of each job.

**Maintenance free** - Periodic cleaning and changing the ribbon cartridge are all that's required.

Available Configuration:

Parallel/USB  
Ethernet 10Base-T/100Base-T

SERIAL MATRIX  
PRINTERS

MOBILE  
PRINTERS

THERMAL  
PRINTERS

LINE MATRIX  
PRINTERS

LASER  
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

## T2348

<b>Print Speed</b>	10 cpi:448 cps (High speed draft) 360 (Draft), 113 (LQ)
<b>Resolution</b>	Graphics 360X360 DPI (ESC/P Emulation only)
<b>Printhead Life</b>	200 million characters
<b>Memory</b>	128Kb
<b>Standard Connectivity</b>	(model variants) Parallel/USB; Ethernet 10BaseT/100Base-T (t.b.a.)
<b>Standard Emulation</b>	Epson ESCP/P2, IBM XL24E
<b>Fonts</b>	Bitmap fonts: Courier 10, Prestige Elite 12, Boldface PS, Compressed, Draft 12, High-speed draft 12, OCR-B 10, OCR-A 10, Correspondence 10, PCIA 10; Scaleable Fonts: Courier, Nimbus Sans®, Timeless (Normal, Bold, Italic)
<b>Consumables</b>	Ribbon: 4 million characters
<b>STD Paper Handling</b>	Auto-tear; manual continuous/cut sheet switch; manual paper thickness adjustment
<b>Paper Type</b>	Continuous forms, cut sheets
<b>Paper Weight</b>	Approximately 7.3 Kg (16 lbs.)
<b>Paper Size</b>	Cut sheet: width 102-267 mm, length 76-364 mm Continuous forms: width 102-267 mm length over 102 mm
<b>Physical Weight</b>	Approximately 9.7 Kg (19 lbs.)
<b>Physical Size</b>	(WxDxH) 415 x 330 x 120 mm
<b>Power Voltage</b>	220 VAC to 240 VAC +10%
<b>Power Consumption</b>	10W max waiting, 70W max average, 180W max
<b>Workload</b>	8,000 pages per month
<b>Number of Copies</b>	Up to 5 part forms
<b>Temperature</b>	5 °C to 35 °C Humidity 20 -80% RH
<b>Humidity</b>	20 - 80% RH
<b>Acoustic</b>	49 dBa
<b>Warranty</b>	2 years, return to base
<b>Option 1</b>	Ethernet 10Base-T / 100Base-T; USB ver. 1.1 Type B