

T2365 MC

Powerful & Rugged for Heavy Duty Operation



Tally

The T2365 MC and T2380 printers are rugged and powerful high speed matrix printers for heavy duty operation under the most extreme conditions. Reliable, heavy workload output is guaranteed for many years following printer purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Low running costs and durability in the harshest of print environments make these products excellent value for money.

- **Up to 9 part forms**
- **Full range of automatic features to minimize user intervention**
- **Ideal for ,On-Demand' and ,Batch' applications with zero tear for no wasted forms**
- **Straight through paper path for easy forms loading**
- **Parallel and Ethernet (10/100BaseT) standard.**
- **Optional Interfaces: RS232 Serial; Coax/Twinax; Ethernet IPDS**
- **Straight through paper path for easy forms loading**
- **Compatible with a wide range of operating systems including Wiindows, UNIX, DOS, SAP R3 and legacy systems**

These products are well matched to Microsoft Windows applications, and highly compatible with other host operation environments including legacy systems.

Fully automated operation, coupled with the ,straight through' paper path, allows ease of use and virtually eliminates errors caused by user intervention.

Available Configuration:

T2365 MC

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

THERMAL PRINTERS

LINE MATRIX PRINTERS

LASER PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

T2365 MC

Print Speed	At 10, 12 cpi: High Speed Draft 640, 800; Draft 533, 640; NLQ 180, 215
Throughput	587 pages per hour (ECMA 132)
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi (Emulation dependent)
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million characters
Memory	128Kb
Standard Connectivity	Bi-directional parallel plus Ethernet 10/100BaseT with 128Kb buffer
Optional Connectivity	RS232 Serial, Adapters, Twinax/Coax, Ethernet IPDS
Standard Emulation	IBM® Proprinter, Epson® LQ (ESC P/2), Genicom ANSI, MTPL + Barcode/LCP
Optional Emulation	PCL3 (rugged writer)
Fonts	HS Draft, Draft, Copy Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, Kix/Royal, OCR A, OCR B, 22 Bar Codes & scaleable LCP
Consumables	Ribbon: 20 million characters
STD Paper Handling	Push tractor with paper parking and AGA
Optional Paper Handling	2nd front tractor (user installable), paper pedestal, paper basket, paper cutting device
Paper Type	Continuous forms
Paper Weight	60-120gsm
Paper Size	100 to 420mm wide
Physical Weight	Approximately 19Kg
Physical Size	(HxWxD): 280x623x432mm
Power Voltage	230V
Power Consumption	60W printing
Workload	48,000 pages per month
Number of Copies	Up to 9 part forms
Temperature	+10° to +35°C
Humidity	20% to 80%
Acoustic	59dB(A)
Warranty	2 years, on-site





Note: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.

DASCOM GB Limited
ViewPoint, Basing View,
Basingstoke, Hampshire RG21 4RG
Tel: +44 (0) 1256 481481
Fax: +44 (0) 1256 481400

www.dascom.com

All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2009 DASCOM Europe GmbH
Ver. 1.0
Printed Date: 01.04.10

SERIAL MATRIX PRINTERS 
MOBILE PRINTERS 
THERMAL PRINTERS 
LINE MATRIX PRINTERS 
LASER PRINTERS 