

## T5040

### Passbook Printer



*Tally*

With up to 600 characters per second (cps), the T5040 rapidly processes media of diverse types ranging from passbooks and cheques to A5 receipts and A4 information sheets.

The printer's flatbed design provides totally assured paper handling, and with advanced features such as Automatic Paper Alignment and Auto Gap Adjustment (AGA), they offer unsurpassed ease-of-use. Using Serial Impact technology - the most reliable and versatile method available of producing print - the T5040 is a durable, robust, dependable printer that supports a wide range of printing applications.

- **Supports a wide variety of media**
- **Automatic gap adjustment of the print head**
- **Automatic alignment of forms and passbooks**
- **Automatic edge detection**
- **Ability to connect to multiple hosts simultaneously via parallel or USB, plus an optional second serial port**
- **Unrivalled transaction times - typical passbook 2.2 seconds**
- **DIN Letter 11.8 seconds**

The standard T5040 supports cut forms via a serial interface connection and a secure command language, as demanded within the banking environment. As standard, TUSB and Parallel interfaces are included for flexibility of connection and single-station, multi-user operation. A second, plug in, serial interface is available as an upgrade option.

Also available are models with Magnetic Stripe encoding for reading accounts codes directly into the system minimising user intervention.

Available Configuration:

T5040 Standard Product

SERIAL MATRIX  
PRINTERS

MOBILE  
PRINTERS

THERMAL  
PRINTERS

LINE MATRIX  
PRINTERS

LASER  
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

## T5040

<b>Print Speed</b>	Draft:300cps; LQ:100cps (normal mode); Draft:400cps; LQ133cps (high speed mode)
<b>Resolution</b>	Resolution (depending on application): Horizontal 60, 80, 90, 120, 180, 240, 360; Vertical 60, 180
<b>Character Density</b>	5, 10, 12, 15, 16.6, 17.1, 20, 24 cpi
<b>Line Density</b>	6 and 8lpi and increments up to 1/360th, inch
<b>Character Sets</b>	IBM PC2 (13 national char sets) ISO 8859-2/-5/-7/-8/-9 additional char sets available from CD ROM
<b>Printhead Life</b>	400 million dots per wire
<b>Standard Connectivity</b>	RS232, 9 pin D-Sub male connector, USB-2, Parallel Centronics IEEE-1284, 32KByte buffer
<b>Optional Connectivity</b>	Models with 2nd Serial RS232 interface are available. TGNNet Ethernet 10/100BaseT adapters
<b>Standard Emulation</b>	Epson ESC/P, IBM 4722, Olivetti PR50/PR2/PR2e, IBM PP XL24e
<b>Fonts</b>	Draft, Roman, Sans Serif, Courier, Bold, Prestige, Script, Orator, Gothic, OCRA/B*
<b>Consumables</b>	Ribbon: 10 million characters
<b>Standard Paper Handling</b>	Document feed - horizontal from the front. Automatic alignment, Automatic loading, Automatic left edge sensing
<b>Paper Type</b>	Passbooks and cut forms: includes labels, cheques, receipts, invoices, information sheets
<b>Forms Thickness</b>	Passbook: 2.0mm max including covers. Paper weight (sewn on pages) 75-120 g/m2
<b>Paper Size</b>	Cut forms: Width:70-240mm; Length:70-500mm; Thickness 60-180 g/m2
<b>Physical Weight</b>	Approximately 10Kg
<b>Physical Size</b>	(HxWxD) 168 x 378 x 280mm
<b>Power Voltage</b>	230V
<b>Power Consumption</b>	max. 73W (printing), 8.9W (sleep), 0W (standby/off)
<b>Workload</b>	1200 documents per day
<b>Number of Copies</b>	Up to 5-part forms
<b>Temperature</b>	+10°C to +30°C
<b>Humidity</b>	15%-75% relative humidity non condensing
<b>Acoustic</b>	Less than 55dB(A)
<b>Warranty</b>	2 years, onsite





Note: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.

**DASCOM GB Limited**  
ViewPoint, Basing View,  
Basingstoke, Hampshire RG21 4RG  
Tel: +44 (0) 1256 481481  
Fax: +44 (0) 1256 481400

[www.dascom.com](http://www.dascom.com)

All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2009 DASCOM Europe GmbH  
Ver. 1.0  
Printed Date: 01.04.10

SERIAL MATRIX PRINTERS   
MOBILE PRINTERS   
THERMAL PRINTERS   
LINE MATRIX PRINTERS   
LASER PRINTERS 