

DWL-P1012



Air Premier[®] 12-Port PoE Midspan

FEATURES

Convenient Installation

- Ideal for Upgrading Existing Network Infrastructure
- 1U Form Factor Allows for Easy Integration Into 19" Switch Racks
- 12-Ports for Delivering Power to Up to 12 802.3af Compliant Network Devices

Top of the Line PoE Performance

- Injector Unit
- Up to 15.4 W Per Port
- Transforms 110-240VAC to Low Voltage DC Power
- Intelligently Detects if Receiving Network Device is 802.3af Compliant
- Works with D-Link DWL-P50 PoE Terminal Unit Adapter

Easy Management

- Web Browser HTTP
- Web-Smart Utility
- SNMP v1 with MIB2, PoE MIB, and Private MIB

D-Link, an industry pioneer in networking solutions, introduces a line of new Power over Ethernet (PoE) Midspans designed to help simplify network maintenance and deployments for small to medium businesses. The D-Link DWL-P1012 is a new 12-port PoE Midspan designed specifically for business-class environments seeking to add secure and manageable power over LAN options.

As network implementations continue to grow within a corporation, hardware integration and management become increasingly complex. This Midspan converts standard 110-240VAC power into low-voltage DC that runs over existing LAN cabling (CAT5 or better) to power up 802.3af compliant network accessories. This DWL-P1012 features 12 integrated 802.3af Power over Ethernet (PoE) ports capable of supplying up to 15.4 watts of power per port. By adding this PoE midspan to existing network infrastructures, installing networking products such as IP telephony devices, Access Points and IP security cameras can be easily managed and set up.

With a 1U 19" form factor, adding the DWL-P1012 to a network switch rack is a straightforward process. From there, delivering power and data to the other 802.3af compliant networking devices simply becomes a plug and play solution just by using standard CAT5 or better Ethernet cables. Wireless device deployments are no longer confined to locations with available power outlets and network administrators no longer need to deal with bulky AC power adapters.

To truly optimize the performance features of multi-port PoE midspans, multiple units of the DWL-P1012 can be deployed to provide a central power source to the entire network LAN infrastructure. This ensures continuous operation during power failures and also eliminates the time and cost of installing separate power cabling and providing a dedicated, uninterrupted power supply for individual terminals and networking devices. Just connect the Midspans to a Uninterruptible Power Supply (UPS) for guaranteed power in case of unforeseen emergencies. The DWL-P1012 also features intelligent PoE awareness, meaning the Midspan will verify that the network device receiving power is 802.3af compliant; otherwise, only data will be sent through the Ethernet wire.

The DWL-P1012 features a management port that can be managed via D-Link's web-based HTTP GUI or through the Web-Smart Utility. Advanced management includes SNMPv1 with MIB2, PoE MIB, and Private MIB. In addition remote access allows monitoring of port level operating status, as well as power shutdown/regulate to a given port.

With simple installation and advanced management tools, the DWL-P1012 PoE Midspan is a cost-effective solution to the business networks seeking to upgrade and simplify their existing network infrastructure.

12-Port PoE Midspan

Specifications

Management

- Web-smart Utility for configuration using Windows PC
- Web-based Configuration for remote management via TCP/IP
- SNMP MIBII, PoE, and Private MIB support
- Monitor PoE Port status through Web-UI

Administration

- Enable or Disable each port individually
- Limit available power to each port
- Assign SNMP events to each port individually
- Save device configuration to local HDD
- Restore device configuration from local HDD
- Upgrade firmware feature
- Restore factory default settings through reset button or Web-Interface

Standards

- 802.3
- 802.3u
- 802.3x
- 802.3af

Physical & Environmental**Interfaces**

- 12 10/100BASE-TX Data-In Ports
- 12 10/100BASE-TX Data and Power Out Ports
- 1 10/100BASE-TX Auto MDI/X Management Port

Diagnostic LED

- 1 Power LED
- 1 System LED
- 1 Max Power LED
- 12 PoE Port Good LED – Green
- 12 PoE Port Fail LED – Red
- 1 Management Port Link LED
- 1 Management Port Speed LED

Power Input

- Internal 250W Power Supply – 100~240VAC 50~60Hz

Power Output

- 48VDC Per Port Output – 15.4W max Per Port
- Total Aggregate Output Power not to exceed 185W
- 12 Ports at full 15.4W output supported
- Total System Power 250W

Power Management

- Auto disable single port if port current is over 350mA while other ports remain active
- Active circuit protection automatically disables the port if there is a short while other ports remain active
- Auto discovery will recognize the connection of PD and immediately supply power to it

Dimensions

- 17.32" L x 8.28" W x 1.75" H

Weight

- 6.6 lbs

Temperature

- Operating: 32°F ~ 104°F
- Storage: -4°F ~ 158°F

Humidity

- Operating: 10 ~ 90% Relative Humidity
- Storage: 10 ~ 95% Relative Humidity

Emission

- FCC Part 15 Class A
- CE Class A
- VCCI Class A

Safety

- UL
- CUL
- CE
- TUV

Warranty

- 1 Year