

## Vision with Precision for Demanding Outdoor HD Security

Sony is pleased to introduce a powerful addition to its network HD camera lineup, the SNC-DH180. This vandal-resistant, wide dynamic range camera is designed with a built-in infrared (IR) illuminator. As a dual-stream network camera, it supports H.264, MPEG-4, and JPEG compression formats, and delivers excellent picture quality in HD 720p resolution at 30 frames per second (fps).

Incorporating the new "Exmor™" CMOS image sensor from Sony, which is specially designed for surveillance applications, this rugged camera features state-of-the-art image-enhancement technology, View-DR, which realizes an extremely wide dynamic range. The SNC-DH180 also features an IR illuminator to deliver quality images even in absolute darkness (0 lx)\*. Along with a host of superb features such as DEPA Advanced, PoE, a built-in heater, and the Easy Focus/Easy Zoom function, the SNC-DH180 Mini Dome Network Camera is ideal for the most demanding surveillance applications.






\* 0 lx requires the use of IR illuminators. IR rays are not visible to the human eye.

### Network HD Mini Dome Camera SNC-DH180

Preliminary


#### FEATURES

- Excellent HD\*1 picture quality, supporting H.264 at 30 fps **HD**
- The new "Exmor" CMOS sensor realizes high image quality and high sensitivity for surveillance **Exmor**. 
- Clearly see objects in the dark up to 15 m (49 feet) away with IR illuminators, which allow the camera to operate in 0 lx\*2 lighting conditions \*3 (Images 1)
- Superior dynamic range using newly developed View-DR (Visibility enhanced wide Dynamic Range) technology (Images 2) **View-DR**
- The Visibility Enhancer optimizes contrast and makes the subject more visible, even in severe backlight or shadow conditions
- XDNR (eXcellent Dynamic Noise Reduction) technology for clear images without motion blur under low illumination (Images 3)
- Easy Focus function/Easy Zoom function
- DEPA Advanced Intelligent Video and Audio Analytics trigger an alarm, based on user-defined rules
  - ▶ Intelligent Motion Detection
  - ▶ Tamper Alarm
  - ▶ Advanced Audio Detection\*4
- Three codecs (H.264, MPEG-4, JPEG) with dual streaming capability
- Power over Ethernet (PoE) capability
- Built-in heater for use in cold
- IP66 Rating
- ONVIF Conformance (Open Network Video Interface Forum) 


\*1 1280 x 720 \*2 0 lx requires the use of IR illuminators. IR rays are not visible to the human eye. \*3 When the IR illuminator is activated, the image is in black and white. \*4 Available with software version 1.1 or later.

#### Drastic Improvement in Visibility

##### IR Illuminator (Images 1)



##### View-DR (Visibility enhanced wide Dynamic Range) (Images 2) **View-DR**



Actual Images

##### XDNR (eXcellent Dynamic Noise Reduction) (Images 3)



Actual Images

Connect Your Vision

**IPELA™**

## SPECIFICATIONS


SNC-DH180	
<b>Camera</b>	
Image device	1/3 type progressive scan "Exmor" CMOS sensor
Minimum illumination	TBD
Number of effective pixels (H x V)	Approx. 1.4 Megapixel (1329 x 1049)
Electronic shutter speed	1 s to 1/10000s
Gain control	Auto (3 levels)/Manual
Exposure control	Auto, EV Compensation *1, Auto Slow Shutter *2
White balance mode	Auto (ATW, ATW-PRO), Preset, One-push WB, Manual
Lens type	Vari-focal lens
Zoom ratio	Optical 2.9X (x2 Digital Zoom)
Horizontal viewing angle	85.4 to 31.2 degrees
Focal length	f=3.1 to 8.9 mm
F-number	F1.2 (wide), F2.1 (tele)
Minimum objects distance	300 mm
Powered Focus	Yes (Easy Focus)
Powered Zoom	Yes (Easy Zoom)
IR Illuminator	Yes (Wave Length: 850nm (Typical), IR LED: 21 pcs)
<b>Camera Features</b>	
Day/Night *3	Yes
Wide-D	View-DR (125dB: Theoretical)
Image enhancement	Visibility Enhancer
Noise reduction	XDNR
<b>Image</b>	
Codec image size (H x V)	1280 x 1024, 1280 x 960, 1280 x 800, 1280 x 720, 1024 x 768, 1024 x 576, 800 x 480, 768 x 576, 640 x 480, 640 x 368, 384 x 288, 320 x 240, 320 x 192 (H.264, MPEG-4, JPEG)
Video compression format	H.264, MPEG-4, JPEG
Codec streaming capability	Dual streaming
Maximum frame rate	H.264/MPEG-4/JPEG: 30 fps (1280 x 720)
<b>Audio</b>	
Audio compression	G.711/G.726
<b>Scene Analytics</b>	
Intelligent motion detection	Yes (with built-in Post Filter)
Intelligent object detection	No
Rule filter	Yes
Intelligent audio detection	Yes *4
<b>Network</b>	
Protocols	IPv4, IPv6, TCP, UDP, ARP, ICMP, IGMP, HTTP, HTTPS, FTP (client/server), SMTP, DHCP, DNS, NTP, RTP/RTCP, RTSP, SNMP (MIB-2)
ONVIF conformance	Yes
Wireless network	No
Number of clients	10
Authentication	IEEE802.1X
<b>Analog Video Output</b>	
Signal system	NTSC / PAL
Horizontal resolution	600 TV lines
S/N ratio	More than 50dB
<b>Interface</b>	
Ethernet	10BASE-T / 100BASE-TX (RJ-45)
Serial interface	No
Card slots	No
Analog video output	BNC x 1, RCA x 1
Sensor input	x 1
Alarm output	x 2
External microphone input	Mini-jack (Monaural), MIC IN/LINE IN: 2.47VDC plug-in power
Audio line output	Mini-jack (Monaural), Max output level: 1 Vrms
<b>General</b>	
Mass	1420 g (3 lb 2 oz)
Dimensions (ø x H)	166 x 119 mm (6 5/8 x 4 3/4 inches)
Power requirements	PoE *5, AC24V, DC12V
Power consumption	23 W max.
Operating temperature *6	-30°C to +50°C (-22°F to 122 °F) (with built in heater)
Storage temperature	-20°C to +60°C (-4°F to 140 °F)
<b>System Requirements</b>	
Operating system	Windows XP, Windows Vista
Processor	Intel Core2 Duo 2 GHz or higher
Memory	1 GB or more
Web browser	Microsoft Internet Explorer Ver6.0 or 7.0
<b>Supplied Accessories</b>	
	CD-ROM (User's Guide, SNC Toolbox), Installation manual, Wire rope, Bracket, BNC cable, I/O cable, Audio cable, M4 shoulder screw, M4 screw x 4, Flyee, L-wrench, B&P Warranty Booklet, Template

\*1 VE off mode only. \*2 View-DR off mode only. \*3 Removable IR Cut Filter.

\*4 Available with software version 1.1 or later. \*5 When used with PoE, SNC-DH180 cannot be used with a heater.  
\*6 Cold start must be greater than -20°C (-4°F) degree.


The SNC-DH180 includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>).

## SYSTEM CONFIGURATIONS



## DIMENSIONS

Unit: mm (inches)



## Distributed by

© 2009 Sony Corporation. All rights reserved.  
 Reproduction in whole or in part without written permission is prohibited.  
 Features and specifications are as of version 1.1 or later and subject to change without notice.  
 The values for weight and dimension are approximate.  
 Sony is a registered trademark of Sony Corporation.  
 IPELA and "Exmor" are trademarks of Sony Corporation.  
 Windows, XP, and Vista are trademarks of Microsoft Corporation.  
 Core is a trademark of Intel Corporation.  
 All other trademarks are the property of their respective owners.