

Itona TC1440

Entry-Level Desktop Thin Client



Itona TC1440

Fully featured

- Windows CE 6 operating system
- AMD® Geode LX600, 366MHz processor
- Very small footprint - 19cm high x 14.2cm deep
- Highly reliable fanless design - very low power consumption
- 256Mb RAM & 128Mb Flash Memory
- 4 USB ports
- In-built 10/100/1000 Networking
- 32 Bit graphics

Green Credentials

With very low average power consumption of 6 watts, the Energy Star 5.0 rated Itona is far more efficient than a PC. It is also substantially lower than the majority of its competitors.

Remote management included

Every Itona comes with the powerful XLmanage remote management software, Workgroup Edition, making central management a breeze.

The new, highly compact Itona TC 1440 desktop is a major breakthrough in the provision of low cost, virtualisation-capable, thin client computing. Measuring only 19cm (7.5") high, this entry level desktop offers an affordable solution combined with advanced features and specification well beyond its rivals.

Built to VXL's exacting specifications, the fan-less design ensures the TC1440 is extremely reliable and together with the energy efficient power supply, achieves a very low average power consumption.

Backed by VXL's comprehensive worldwide support network and an impressive three year warranty, the new Itona represents an unbeatable combination of affordability, performance, quality and service.



About VXL

VXL is one of the world's largest suppliers of thin clients. Established in 1976, VXL has grown steadily and now has over three hundred people worldwide - with offices in Germany, France, India, the United States and the United Kingdom. The company's headquarters are in Bangalore, India.



CITRIX partner

Solution Partner



Itona TC1440

Part No
TC1440 - F3R4 128 MB Flash / 256 MB RAM

Model

TC1440 Windows CE 6.0 R2,
Citrix ICA client, Citrix PN
Agent, RDP 6.0 Resident.

Processor

- AMD Geode LX600 366MHz Processor

System Memory

- Ram: 256Mb
- Flash: 128Mb

Display Support

- Display Data Control (DDC) for automatic setting of resolution and refresh rate
- Video RAM: 8/16/32/64 MB. Selectable from BIOS (default 16MB). Display res. 4:3 up to 1600 x 1200 32bit colour. Widescreen up to 1680 x 1050 32bit colour.

Interfaces

- 4 x USB 2.0
- One VGA type video output
- Built-in Kensington Security Slot

Networking

- Autosensing, 10/100/1000 Ethernet, RJ-45
- Wake On Lan
- PXE boot

Audio

- Line Out
- Mic

Environmental

- Temperature Range :
Powered on: 5 to 35 °C
Powered off: -20 to 60 °C
- Convectional cooling, fanless design
- Humidity : 20% to 80% maximum, non-condensing

Physical Characteristics

- External power adapter with full range
- autosensing AC adapter (100/240 V) for worldwide usage
- Height: 190 mm
- Depth: 142 mm
- Width: 36.5 mm
- Weight: Approx 0.7Kg

Software

- Citrix ICA client 10.xx
- RDP Client : A Remote Desktop Protocol 6.0

Local Operating System Features

- Password-protected support

Server OS Compatibility/Support :

- Microsoft Windows Terminal

Server Edition, Windows 2003 / 2008

- Citrix XenApp / Citrix Presentation Server/ Citrix XenDesktop.
- Protocol Support : TCP/IP, NTP, DHCP, FTP, HTTP

Management:

- Remote management, configuration, and upgrades through XLmanage client management software (included)
- Wake terminal remotely (Wake-on-LAN)
- Terminal configuration (IP information, name, etc.)
- Send messages
- Remote Shadowing
- Complete image upgrade
- Pull/Push Updates

Regulatory Compliance

- Europe: CE, TUV-GS
- US/Canada: cULus, FCC B
- Environmental: CE, RoHS, WEEE, Energy Star 5.0

Warranty

- Three years limited warranty



Head Office: 'House of Excellence', No 17 Electronics City, Hosur Road, Bangalore 560 100, India
Tel: +91 80 30222525 (5 lines) **Fax:** +91 80 28520095 **E-mail:** sales@vxl.net **Web:** www.vxl.net
European Headquarters: Carrington Business Park, Carrington, Manchester, UK M31 4DD
Tel: +44 (0) 16 17 75 47 55 **Fax:** +44 (0) 16 17 75 48 66 **E-mail:** sales@vxl.net

Regional Offices

France

Tel: +33 (0) 1 42 17 00 03
E-mail: sales@vxl.net

Germany

Tel: +49 (0) 8761 1093
E-mail: sales@vxl.net

United States

Tel: +1 713 589 3273
E-mail: sales@vxl.net