

Itona TC1536

Mid-Range Desktop Thin Client



Itona TC1536

Fully featured

- VMware Virtualisation ready
- Linux GIO2 operating system
- ViA C7-M processor (North Bridge: VIA VX855)
- Very small footprint - 19cm high x 14.2cm deep
- Highly reliable fanless design - very low power consumption
- 512 Mb RAM & 512 Mb Flash Memory
- 5 USB ports
- In-built 10/100/1000 Networking
- 32 Bit graphics

Green Credentials

With very low average power consumption of 8 watts, the Energy Star 5.0 rated Itona is far more efficient than a PC. It is also substantially lower than the majority of its competitors.

Remote management included

Every Itona comes with the powerful XLmanage remote management software, Workgroup Edition, making central management a breeze.

The new, highly compact Itona TC 1536 desktop is a major breakthrough in the provision of low cost, virtualisation-capable, thin client computing. Measuring only 19cm (7.5") high, this mid-range desktop offers an affordable solution combined with advanced features and specification well beyond its rivals. For example, the TC1536 incorporates the VMware View client as standard making it "virtualisation ready".

Built to VXL's exacting specifications, the fan-less design ensures the TC1536 is extremely reliable and together with the energy efficient power supply, achieves a very low average power consumption.

Backed by VXL's comprehensive worldwide support network and an impressive three year warranty, the new Itona represents an unbeatable combination of affordability, performance, quality and service.



About VXL

VXL is one of the world's largest suppliers of thin clients. Established in 1976, VXL has grown steadily and now has over three hundred people worldwide - with offices in Germany, France, India, the United States and the United Kingdom. The company's headquarters are in Bangalore, India.



CITRIX partner

Solution Partner



Itona TC1536

Part No
TC1536 - F5R5 512 GB Flash / 512 GB RAM

Model

TC1536 Linux GIO2 Operating System.

Standard Client Software

XDMCP, ICA, PN Agent, RDP, VNC, VMware View Client, REXEC standard, PPTP VPN, Mozilla Browser, Open Office, SAP Client

Processor

- VIA C7-M Processor (North Bridge: VIA VX855)

System Memory

- Ram: 512 Mb & Flash: 512 Mb

Display Support

- Display Data Control (DDC) for automatic setting of resolution and refresh rate
- Video RAM: 32/64/128 MB. Selectable from BIOS (default 32MB). Display res. 4:3 up to 1920 x 1440 32bit colour. Widescreen up to 1920 x 1200 32bit colour.

Interfaces

- 5 x USB 2.0
- 1 x DVI-I port
- Built-in Kensington Security Slot
- Optional Internal USB Wireless LAN.

Networking

- Autosensing, 10/100/1000 Ethernet, RJ-45
- Wake On Lan
- PXE boot

Audio

- Line Out
- Mic

Environmental

- Temperature Range : Powered on: 5 to 35 °C

- Powered off: -20 to 60 °C
- Convectional cooling, fanless design
- Humidity : 20% to 80% maximum, non-condensing

Physical Characteristics

- External power adapter with full range
- autosensing AC adapter (100/240 V) for worldwide usage
- Height: 190 mm
- Depth: 142 mm
- Width: 36.5 mm
- Weight: Approx 0.7Kg

Software

- Citrix ICA client 11.xx
- RDP Client : A Remote Desktop For Linux 1.6.0, RDP6 x Compatible
- Mozilla Browser with Multimedia Java, other plugin support
- Open Office
- SAP Client
- Ericom Blaze
- Ericom Webconnect
- NX Client
- Quest Access Client
- VMware View Client
- PPTP VPN
- VNC Client
- VNC Shadowing
- SAMBA Support
- Leostream Client
- XDMCP Protocol: Remote X connection based on X server.
- ThinPrint Client Agent
- Rexec command, RSH, SSH, LaunchPA , telnet, CMD standard

Local Operating System feature :

- Updated Kernel 2.6xx
- X11R6 local windows manager
- LPR, ThinPrint, CUPS, SAMBA print

support

- Touch screen support

Server OS Compatibility/Support :

- Microsoft Windows Terminal Server Edition, Windows server 2003 / 2008
- Citrix XenApp / Citrix Presentation Server/ Citrix XenDesktop.
- UNIX/Linux Servers (Redhat etc)
- Protocol Support :TCP/IP, NTP, DHCP, FTP, HTTP

User Interface:

- Boot from Local flash
- User Interface Language: US English, French, German
- Keyboard language support: U.S. English Standard, French, German, Italian, U.K English, 30 others included.

Management:

- Remote management, configuration, and upgrades through XLmanage client management software (included)
- Wake terminal remotely (Wake-on-LAN)
- Terminal configuration (IP information, name, etc.)
- Remote Shadowing
- Complete image upgrade
- Pull/Push Updates

Regulatory Compliance

- Ergonomics: German EKI-ITB 2000
- Safty: cTUVus, TUV-GS,
- RF Interference: FCC B, CE, RoHS, WEEE, Energy Star 5.0

Warranty

- Three years limited warranty



vmware® | technology alliance
PARTNER



CITRIX® partner

Solution Partner



Head Office: 'House of Excellence', No 17 Electronics City, Hosur Road, Bangalore 560 100, India
Tel: +91 80 30222525 (5 lines) **Fax:** +91 80 28520095 **E-mail:** sales@vxl.net **Web:** www.vxl.net
European Headquarters: Carrington Business Park, Carrington, Manchester, UK M31 4DD
Tel: +44 (0) 16 17 75 47 55 **Fax:** +44 (0) 16 17 75 48 66 **E-mail:** sales@vxl.net

Regional Offices
France

Tel: +33 (0) 1 42 17 00 03
E-mail: sales@vxl.net

Germany

Tel: +49 (0) 8761 1093
E-mail: sales@vxl.net

United States

Tel: +1 713 589 3273
E-mail: sales@vxl.net