

# Itona TC1540

## Mid-Range Desktop Thin Client



### Itona TC1540

#### Fully featured

- Windows CE 6 operating system
- VIA C7-M processor (North Bridge: VIA VX855)
- Very small footprint - 19cm high x 14.2cm deep
- Highly reliable fanless design - very low power consumption
- 512 Mb RAM & 128 Mb Flash Memory
- 5 USB ports
- In-built 10/100/1000 Networking
- 32 Bit graphics

#### Green Credentials

With very low average power consumption of 8 watts, the Energy Star 5.0 rated Itona is far more efficient than a PC. It is also substantially lower than the majority of its competitors.

#### Remote management included

Every Itona comes with the powerful XLmanage remote management software, Workgroup Edition, making central management a breeze.

The new, highly compact Itona TC 1540 desktop is a major breakthrough in the provision of low cost, virtualisation-capable, thin client computing. Measuring only 19cm (7.5") high, this mid-range desktop offers an affordable solution combined with advanced features and specification well beyond its rivals.

Built to VXL's exacting specifications, the fan-less design ensures the TC1540 is extremely reliable and together with the energy efficient power supply, achieves a very low average power consumption.

Backed by VXL's comprehensive worldwide support network and an impressive three year warranty, the new Itona represents an unbeatable combination of affordability, performance, quality and service.



### About VXL

VXL is one of the world's largest suppliers of thin clients. Established in 1976, VXL has grown steadily and now has over three hundred people worldwide - with offices in Germany, France, India, the United States and the United Kingdom. The company's headquarters are in Bangalore, India.



**CITRIX** partner

Solution Partner



# Itona TC1540

Part No  
TC1540 - F3R5 128 MB Flash / 512 MB RAM

## Model

**TC1540** Windows CE 6.0 R2.

## Standard Client Software

Citrix ICA client, Citrix PN Agent, RDP 6.0 Resident

## Processor

- VIA C7-M Processor (North Bridge: VIA VX855)

## System Memory

- Ram: 512 Mb & Flash: 128 Mb

## Display Support

- Display Data Control (DDC) for automatic setting of resolution and refresh rate
- Video RAM: 32/64/128/256 MB. Selectable from BIOS (default 32MB). Display Res. 4:3 up to 1920x1440 32bit colour. Widescreen up to 1920 x 1200 32 bit colour.

## Interfaces

- 5 x USB 2.0
- 1 x DVI-I port
- Built-in Kensington Security Slot
- Optional Internal USB Wireless LAN.

## Networking

- Autosensing, 10/100/1000 Ethernet, RJ-45
- Wake On Lan
- PXE boot

## Audio

- Line Out

- Mic

## Environmental

- Temperature Range :  
Powered on: 5 to 35 °C
- Powered off: -20 to 60 °C
- Convectional cooling, fanless design
- Humidity : 20% to 80% maximum, non-condensing

## Physical Characteristics

- External power adapter with full range
- autosensing AC adapter (100/240 V) for worldwide usage
- Height: 190 mm
- Depth: 142 mm
- Width: 36.5 mm
- Weight: Approx 0.7Kg

## Software

- Citrix ICA client 10.xx
- RDP Client : A Remote Desktop Protocol 6.0
- Media Player Ver 9.0
- Thin Print Client Agent
- MSN Messenger
- Pocket word
- SMART CARD
- Password-protected support

## Server OS Compatibility/ Support :

- Microsoft Windows Terminal Server Edition, Windows 2003 / 2008
- Citrix XenApp / Citrix Presentation Server/ Citrix XenDesktop
- Protocol Support : TCP/IP, NTP, DHCP, FTP, HTTP

## User Management:

- Boot from Local flash
- Users Profile for Connections and Configure Access to Control panel component
- Windows CE.Net user interface Keyboard interface Language & Keyboard: U.S. English, U.K.English, French, German, Spanish, plus other 26 languages included

## Management:

- Remote management, configuration, and upgrades through XLmanage client management software (included)
- Wake terminal remotely (Wake-on-LAN)
- Terminal configuration (IP information, name, etc.)
- Send messages
- Remote Shadowing
- Complete image upgrade
- Pull/Push Updates

## Regulatory Compliance

- Ergonomics: German EKI-ITB 2000
- Safety: cTUVus, TUV-GS,
- RF Interference: FCC B, CE, RoHS, WEEE, Energy Star 5.0

## Warranty

- Three years limited warranty



**Head Office:** 'House of Excellence', No 17 Electronics City, Hosur Road, Bangalore 560 100, India  
**Tel:** +91 80 30222525 (5 lines) **Fax:** +91 80 28520095 **E-mail:** sales@vxl.net **Web:** www.vxl.net  
**European Headquarters:** Carrington Business Park, Carrington, Manchester, UK M31 4DD  
**Tel:** +44 (0) 16 17 75 47 55 **Fax:** +44 (0) 16 17 75 48 66 **E-mail:** sales@vxl.net

## Regional Offices

### France

Tel: +33 (0) 1 42 17 00 03  
E-mail: sales@vxl.net

### Germany

Tel: +49 (0) 8761 1093  
E-mail: sales@vxl.net

### United States

Tel: +1 713 589 3273  
E-mail: sales@vxl.net